







## ABS Coin Tag – Black -Product Spec.

							
OD22/T2.4mm	OD30/T3mm	OD30/ID3/T2mm	OD30/ID5/T2mm				
							
OD50/ID5/T2mm	OD50/ID5/T5mm	OD52/ID5.7/T8.2mm					
IC	EM*	TEMIC (T5567)	Mifare Ultralight	Mifare 1S50	Mifare 1S70	TI Tag-it	ICode2
Memory	64 bits	330 bits	512 bits	1 K bytes	4 K bytes	2K bits	1024 bits
Function	Read Only	Read / Write					
Dimensions	OD22 / T2.4mm (w/o hole)						
	OD30 / T3mm (w/o hole)						
	OD30 / ID3 / T2mm						
	OD30 / ID5 / T2mm						
	OD50 / ID5 / T2mm						
	OD50 / ID5 / T5mm						
	OD52 / ID5.7 / T8.2mm						
Frequency	125 KHz		13.56 MHz				
Operation Temperature	0°C ~ 70°C						
Storage Temperature	-20°C ~ 70°C						
Material	ABS						
Weight	1.5 ~ 2.8 g						
Surface	Matte						
Standard color	Black						

\*EM4200 (Replace EM4100, EM4102) / TK4100